


Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRF 272 RT 55°
- **Nitta Japan code:**
VRT-14A



Construction:	2 plies polyester, rigid		
Material:	TOP COVER PVC	INNER LAYER PVC	BOTTOM SIDE Fabric
Thickness:	2	-	mm (approx.)
Colour:	Nitta colour	Nitta colour	-
Hardness:	55 Shore A	-	-
Profile:	RT	-	-
Total thickness:	6		mm (approx.)
Weight:	4,2		kg/m ² (approx.)
Max. width:	2000		mm
Belt support:	Sliderbed (Rollers), Flat		
Rating at 1% elongation:	8		N/mm
Advised pretension:	4 - 7		N/mm
Maximum allowable tension:	17		N/mm
Temperature range:	-10	to +80	°C
Minimum pulley diameters:			
Flexing:	50		mm
Backflexing:	75		mm
Special approval:	Not applicable		
Applications:	Inclined or declined conveyors Conveying of (corrugated) cardboard boxes		

Date of issue 21-03-2014-1